

CARCOOLANT BS6580 ARO

Material Group: 304193

APRIL 2016

Description: Dark blue clear liquid

<u>Test</u>	<u>Specification</u>	<u>Method</u>
Density @ 20°C (kg/l)	1.127 - 1.141	ASTM D5931
Reserve Alkalinity (ml HCl 0.1N)	2.0 - 3.6	ASTM D1121
pH @ 20°C 33% vol	8.0 - 9.0	ASTM D1287
pH @ 20°C 50% vol	8.0 - 9.0	ASTM D1287
Water, apparent (%wt)	8.0 max	ASTM D1123
Freezing Point, 50% vol (°C)	-33.0 max	ASTM D1177
Foam test @ 88°C - volume (ml)	50 max	ASTM D1881
Foam test @ 88°C - break time (sec)	5 max	ASTM D1881

Product contains a bittering agent

Revision 00

Whilst we believe this data to be correct and reliable, we are not responsible for its interpretation and its use, nor should it be construed as a permission to use any product or process in breach of existing patents. This data does not constitute any warranty other than conformity of the product to current specifications published by the sellers or its suppliers. Any relevant legislation governing the use of the product should be observed.

Univar Local Conditions of Sale apply to sales of all products

Refer to the appropriate Safety Data Sheet for health, safety and environmental information