

Univar Gear Oil U2 80W-90

Description

This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:

- excellent resistance against oxidation.
- a very high activity against wear, corrosion and foaming.
- a low pour point.
- very good EP-properties.

Application

This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

This product is also suitable when the following viscosities are prescribed: SAE 90, 85W-90.

Specifications

Performance level:

API GL-5

MIL-L-2105D

MAN 342 Typ M2

ZF TE-ML 05A/7A/12E/16B/16C/17B/19B/21A

Typical Physical Characteristics

Density at 15 °C, kg/l	0,892
Viscosity 40 °C, mm ² /s	150,5
Viscosity 100 °C, mm ² /s	15,2
Viscosity Index	102
Flash Point COC, °C	214
Pour Point, °C	-27

Advice

Advice on applications not covered in this leaflet may be obtained from your Univar representative

Health, Safety & Environment

Guidance on Health & Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.univarlubricants.no www.univarlubricants.se www.univarlubricants.dk www.univarlubricants.fi